

TECHNICAL INFO SHEET

Product name:	MAX PRO 51 Power-Clean Spray		
Product description:	MAX PRO 51 Power-Clean Spray is a professional and powerful degreaser for applications in industry, construction, the hotel and catering trade, food, non-food and the automotive sector.		
Properties:	 neutral, leaves no residues or greasy film does not deteriorate the surface works very fast and dries very fast can be used on most surfaces* 		
Application:	 for cleaning most surfaces with stubborn soiling and/or grease such as metals, woods, most synthetics, vinyl, glass, ceramics, PVC, plexiglass and polystyrene. Removes oil, grease, dirt, resin, varnish, non-cured polyurethane, non-cured polymers, printing ink, paraffin, meat residues, grease residues, glue residues, stickers, contact adhesive. removes oil and grease spray without disassembly and brake fluid with the assembly and disassembly of brakes, couplings, transmissions and machine parts 		
Packaging:	Aerosol:		500 ml
	Outer boxes:		12 per box
Technical information:	hnical information: Max PRO 51 Power-Clean Spray		
Boiling point/boiling range: Relative density (20°): Physical state (20°): Flash point: Spontaneous combustion: Water solubility: Odour Dynamic viscosity mPa.s/20°C: Kinematic viscosity mm²/S/20°C: Volatile organic compound (VOC) %: Shelf life:		·	ars in unopened packaging if stored e between and +5°C + 25°C.





TECHNICAL INFO SHEET

Processing:	 Spray MAX PRO 51 Power-Clean Spray on the surface to be cleaned and wipe off with a cloth. Allow to fully evaporate before gluing Clean hands after use with MAX PRO 54 Ultra-Cleaning Tissues. see the technical information sheet before use 		
Safety and transport:	See safety sheet		
Guarantee:	D-MAX byba guarantees that its product conforms with the specifications during the shelf life. Liability can never amount to more than determined in our general conditions of sale. Under no circumstances is the seller liable for any consequential damage.		
Liability:	The information provided is the result of our tests and experience and is of a general nature. It does, however, involve no liability. It is the responsibility of the user to establish by his own tests whether the product is suitable for the application.		

^{*} With soft synthetics and/or delicate surfaces always test beforehand.

Sealing & Bonding Solutions

