## **DECLARATION OF PERFORMANCE**





Nr. 2.1

**Identification code of product type:**Dry pressed, extruded ceramic tiles

Group  $Al_{\rm b}$  attachment A, group  $All_{\rm a-Teil\ 1}$  attachment B and

group Blaattachment H

**Intended use:** For internal and external walls

Manufacturer: Ströher GmbH, Ströherstraße 2–10, 35683 Dillenburg, Germany

System(s) of assessment and verification of constancy of performance in accordance

with attachment V:

Systems 4

Harmonized norm: DIN EN 14411, 2016

## **DECLARED PERFORMANCES:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 <sub>FL</sub>	EN 14411: 2016
Release of dangerous substance, for:		
- Cadmium	no performance determined	EN 14411: 2016
- Lead	no performance determined	EN 14411: 2016
- other	no performance determined	EN 14411: 2016
Durability for:		
- internal use	passed	EN 14411: 2016
- external use: freeze-thaw resistance	passed	EN 14411: 2016
Tactility	no performance determined	EN 14411: 2016
Bond stregnth/adhesion, for:		
- cementitious mortar, type C1	≥ 0,5 N/mm <sup>2</sup>	EN 14411: 2016
- dispersion adhesive	no performance determined	EN 14411: 2016
- reaction resin adhesives	no performance determined	EN 14411: 2016
– mortar	no performance determined	EN 14411: 2016
Thermal shock resistance	passed	EN 14411: 2016

The performance of the product is in conformity with the declared performances. This declaration of performance is issued under the sole responsibility of the above manufacturer.

Signed for and behalf of the manufacturer by:

Ströher GmbH
Ströherstraße 2-10
35687 Dillenburg
Telefor +49 2771 391-0
Telefax: +49 2771 391-340
E-Mail: info@stroeher.de
i. V. Jochen Keilwww.stroeher.de
Laboratory head

Dillenburg, June 2017