DECLARATION OF PERFORMANCE





Nr. 1.2

1. Identification code of product type: Dry pressed, extruded ceramic tiles

Group Al_{b} attachment A, group $All_{a\text{-Teil}\,1}$ attachment B and

group Bl attachment H

For internal and external floorings

Ströher GmbH, Ströherstraße 2–10, 35683 Dillenburg, Germany

4. System(s) of assessment and verification of constancy of performance in accordance

with attachment V:

2. Intended use:

3. Manufacturer:

Systems 4

5. Harmonized norm: DIN EN 14411, 2012

6. DECLARED PERFORMANCES:

Essential characteristics	Performance
Reaction to fire	A1 _{FL}
Release of dangerous substance, for:	
- Cadmium	no performance determined
- Lead	no performance determined
- other	no performance determined
Durability for:	
- internal use	passed
- external use: freeze-thaw resistance	passed
Breaking load*	≥ 950 N
Slip resistance properties	
CEN/TS 16165 attachment A; DIN 51131	see current delivery range
Tactility	no performance determined
Bond strength/adhesion, for:	
- cementitious mortar, type C1	≥ 0,5 N/mm ²
- dispersion adhesive	no performance determined
- reaction resin adhesives	no performance determined
- mortar	no performance determined
Thermal shock resistance	passed

7. The performances of the above mentioned product correspond to the declared performances. This declaration of performance was issued in accordance with (EU) Regulation No. 305/2011 under the sole responsibility of the manufacturer stated above.

Signed for and behalf of the manufacturer by:

Ströher GmbH
Ströherstraße 2-10
35687 Dillenburg
Teleco +49 2771 391-0
felefax: +49 2771 391-340
E-Mail: info@stroeher.de
i. V. Jochem Keilwww.stroeher.de
Laboratory head