



TECHNICAL FEATURES

MODEL: WOODLAND	DATE: 04/05/18
SIZE: 25X100	
PRODUCT TYPE: PORCELAIN TILES	
GROUP: B Ib	

TESTS CARRIED OUT	RESULTS	
UNE-EN ISO 10545-2 DIMENSIONS AND SURFACE QUALITY		CONFORMS TO STANDARD
UNE-EN ISO 10545-3 WATER ABSORPTION	AVERAGE VALUE (%)	0,5 - 3%
UNE-EN-ISO 10545-4 MODULUS OF RUPTURE	BREAKING STRENGTH (N)	1800 - 2400 N
	MODULUS OF RUPTURE (N / mm ²)	35 - 45 N/mm²
UNE-EN ISO 10545-8 LINEAR THERMAL EXPANSION	COEFFICIENT (10 ⁻⁶ / °C)	< 7 x 10⁻⁶°C
UNE-EN ISO 10545-9 RESISTANCE TO THERMAL SHOCK	THERMAL SHOCK	RESISTS
UNE-EN ISO 10545-10 HUMIDITY EXPANSION	HUMIDITY EXPANSION (mm/m)	< 0,1 mm/m
UNE-EN ISO 10545-12 FROST RESISTANCE	RESULT	RESISTS
UNE-EN ISO 10545-13 CHEMICAL RESISTANCE	AMMONIUM CHLORIDE 100 g/l	GA
	SODIUM HYPOCHLORITE 20 mg/l	GA
	HYDROCHLORIC ACID 3 %	CONFORMS
	CITRIC ACID 100 g/l	TO
UNE-EN ISO 10545-14 STAIN RESISTANCE	POTASSIUM HYDROXIDE 30 g/l	STANDARD
	GREEN AGENT IN LIGHT OIL	5
	IODINE SOLUTION IN ALCOHOL	5
	OLIVE OIL	5

OBSERVATIONS:	LABORATORY:
---------------	-------------