

peronda

FS NORWICH

| | |
|------------|----------------------------------|
| Model: | FS NORWICH |
| Reference: | 22058 |
| Size: | 33X33 cm |
| Thickness: | 9,5000 mm |
| Finish: | Natural |
| Material: | PORCELANICO - GRUPO Bla - |

Water absorption

| | | |
|----------------|------------------|-------------------|
| EN ISO-10545-3 | Water absorption | < 0,5 % |
|----------------|------------------|-------------------|

Dimensional characteristics

| | | |
|----------------|-----------------------|---------------------------|
| EN ISO-10545-2 | Surface appearance | > 95% |
| EN ISO-10545-2 | Curvature | ± 0,5 % / ± 2,0 mm |
| EN ISO-10545-2 | Thickness | ± 5% / ± 0,5 mm |
| EN ISO-10545-2 | Length | ± 0,6 % / ± 2,0 mm |
| EN ISO-10545-2 | Squareness | ± 0,5% / ± 2,0 mm |
| EN ISO-10545-2 | Straightness of sides | ± 0,5 % / ± 1,5 mm |

Mechanical characteristics

| | | |
|-----------------|--------------------------|----------------------|
| EN ISO 10545-11 | Resistance to crazing | Cumple |
| EN ISO 10545-12 | Resistance to crazing | Cumple |
| EN ISO 10545-9 | Thermal shock resistance | Cumple |
| EN ISO-10545-4 | Breaking strength | > 1300 N |
| EN ISO-10545-4 | Bending strength | > 35 N/mm2 |

Surface characteristics

| | | |
|----------------|-------------------------------|------------------|
| EN ISO 10545-7 | Bending strength | 4 |
| EN ISO 10545-7 | Visible effect at revolutions | 2100 rev. |
| EN-101 | Scratch resistance | 7 |

Chemical characteristics

| | | |
|-----------------|--|--------------------|
| EN ISO-10545-13 | Acids & alkalis at high concentrations | GHA/GHA/GHA |
| EN ISO-10545-13 | Acids & alkalis at low concentrations | GLA/GLA/GLA |
| EN ISO-10545-13 | Household cleaning products | GA/GA |

peronda

FS NORWICH

Model: **FS NORWICH**
Reference: **22058**
Size: **33X33** cm
Thickness: **9,5000** mm
Finish: **Natural**
Material: **PORCELANICO - GRUPO Bla -**

Chemical characteristics

| | | |
|-----------------|------------------|----------------|
| EN ISO-10545-14 | Stain resistance | 5/-/5/5 |
|-----------------|------------------|----------------|

Non-slip characteristics

| | | |
|---------------|--|-----------------|
| ANSI A137 | Stain resistance | >0,42 |
| BS-7976-2 | Stain resistance | +25-35 |
| DIN-51130 | Critical slip angle, shod foot on sloping ramp | R-9 |
| UNE-ENV-12633 | Critical slip angle, shod foot on sloping ramp | 1 |

CE MARKING



CE Declaration of Performance: **001CPR2017-08-01**

Before laying the tiles, check the shade, calibre and quality. No claims will be accepted once the tiles have been laid. Leave a tile joint of at least 0.5 mm in the case of rectified tiles and 1.5 mm for non-rectified ones. The tile colour shown in this data sheet is merely indicative and it might differ from the real tile colour. This document is purely for sales purposes and it cannot be used in any legal or administrative proceedings, in a witness statement or as documentary proof without the express permission of