

MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH
ZIEGELTALSTRASSE 2
D-93346 IHRLEINSTEIN
TELEFON 09441-176940
TELEFAX 09441-1769499
www.moellerstonecare.eu
info@moellerstonecare.eu

MOELLER STONE CARE



PRODUCT SPECIFICATION

HMK® P709 - SILICATE FLUID FOR TERRAZZO FOR PROFESSIONAL USE

- for hardening the surface of terrazzo, concrete screeds, concrete paving and garden ornaments
- increases resistance to wear and reduces dust

HMK® P709 is a ready to use surface reinforcing agent that increases the resistance to wear and hardens the surface of terrazzo, concrete blocks, concrete screed, garden ornaments etc... Treated areas become more resistant to friction wear and less dusty. The color and gloss of the stone are not significantly affected. HMK® P709 is not suitable for use on fine honed and polished natural stones, ceramic and porcelain tiles. For internal and external use.

Instructions: If under floor heating exists, switch it off and allow the surface to cool. Clean the area to be treated thoroughly and allow it to dry (max. 6-8% moisture). Apply HMK® P709 thinly and evenly with a soft brush, small roller with short fibres or a spray. Remove excess HMK® P709 completely after approx. 10 minutes with a rubber squeegee. Surfaces which should not be treated (e.g. walls, glass, furnishings etc...) must be protected. For particularly absorbent surfaces re-apply after 10-20 minutes. To clean surface thoroughly before treatment use HMK® R155 Intensive Cleaner - acid free. For regular cleaning and continued protection use HMK® P324 Liquid Stone Soap, a no-rinse natural product. In order to reduce the penetration of dirt and water into the surface use HMK® S232 Stain Protection - water based.

Coverage: About 3-10m² per litre.

Warning: Chemical product. Do not walk on treated surfaces until the treatment is complete. The effectiveness of HMK® P709 will develop over a 48 hour period. Do not allow the treated surface to become wet during this period. Keep out of the reach of children and safe from frost.

Packaging: 2 x 5 litre cans/box.

Storage: Store in cool dry place.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12° and above 25°C.

Limitation of liability: The liability of HMK® Moeller Stone Care for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stone Care shall not be liable for any consequential damages. No other warranty or representation is made or implied.